Specifications

glassWALLS > Chameleon

Minimal sightlines and extrusions paired with our magnetic panel connections make the glassWALLS > Chameleon system a unique solution to any office front, cladding application, or design. With a multitude of door and opening options, configurations for dividing spaces are essentially endless. The Chameleon frame extrusion is composed of a four-sided channel that facilitates easy installation and customization. Benefits also include ADA compliant features and accessories, easy maintenance and a wide range of metal finishes that can complement CARVART's glass offering. The system also integrates seamlessly with CARVART's glassPOST accessories that allow designers to further customize spaces and add functionality.

VALUE-ADDED BENEFITS

- Multiple door and opening options
- Wide range of CARVART pulls available
- Four-sided channel makes customization easy
- Multiple metal finishes available
- ADA compliant hardware and configurations available
- Power and data integrated cable management
- System durability and long-term integrity
- Turnkey project services

FACILITY DESIGN APPLICATIONS

Space separation, open space configurations, door and opening division, space division between offices, conference rooms or flex-space and cladding.

CONFIGURATIONS

Straight runs, endless fixed panel, custom angles and configurations, various heights, fronts only, 2-4 sided office arrangements.

FUNCTION

Fixed panels, hinged/pivot/sliding door integration available.

GLASS TYPES

Refer to CARVART's Glass Collection

GLASS THICKNESS —

Refer to local code and structural requirements
Accommodates 3/8" nominal up to 1/2" nominal.

HARDWARE DIMENSIONS

Aluminum extrusion height: 2"
Aluminum extrusion depth: 2"

HARDWARE MATERIALS/FINISHES —

Refer to Finish Chart

WIDTHS — OVERALL MINIMUM/ MAXIMUM RANGE (inches):

Glass Panels: Minimum 6" and maximum 48"

(custom and larger sizes available upon request and depending on engineering limits).
Maximum opening lengths: Unlimited.

HEIGHTS — OVERALL MINIMUM/ MAXIMUM RANGE (inches):

Minimum 9" height; maximum 108" height above finished floors (custom and larger sizes available upon request and depending on engineering limits).

MOUNTING FASTENERS

Final anchoring decision is client-directed or based on client structural consultant.

Mounting fasteners and anchors to be supplied by others.
CARVART advisory and coordination available.

WEIGHT & STRUCTURAL LOADS —

Consult local engineer for structural codes and requirements
Sliding door track capacities rated for 200 lbs.

Overall weights available upon request for client structural calculations.
Refer to CARVART for technical consultation.

ADD-ON DESIGN OPTIONS —

Per specification and upcharges apply

Pulls, swing and sliding doors, glassPOST integration.

CUSTOMIZATION

Custom dimensions per opening.

INSTALLATION

Extrusions and adjustable levelers facilitate easy installation and glass loading.

Requires trained and competent glazing or carpenter industry professionals.

Installation instructions, assistance and training available at time of order.

All hardware components, including doors, will be delivered knocked down and require assembly by a glazing industry professional. Certain glass and hardware finishes are available as preassembled products as called out in the glass and hardware finishes pages. Consult a CARVART agent for information on available pre-assembled components.

For more info, contact CARVART

Sales Advisory Team at quotes@carvart.com or call us at 212 675 0030.